



FS-Mountings
type 10-FS-001
Max. 1200 kg - 18 mm - 4Hz

FS-Mountings are designed for floating floors and ‘two-mass’ systems. FS-Mountings have high deflection capabilities and offer superior acoustic performance. Natural frequencies can reach as low as 4 Hz. These mountings are produced from a low creep / high stability elastomer compound and are available in a variety of rubber hardness. For the selection of these mountings we advise you to consult our engineers.

Applications: floating floors, ‘two-mass’ systems etc.

| Dimensions | | | | | |
|------------------|--------|--------|-----------|------------|----------|
| Type Nr. | Ø [mm] | H [mm] | Load [kg] | Defl. [mm] | Hardness |
| 10-FS-50x50-55 | 50 | 50 | 150 | 6 | 55 SH. |
| 10-FS-75x50-55 | 75 | 50 | 250 | 6 | 55 SH. |
| 10-FS-100x70-55 | 100 | 70 | 600 | 7 | 55 SH. |
| 10-FS-100x100-55 | 100 | 100 | 500 | 10 | 55 SH. |
| 10-FS-150x100-55 | 150 | 100 | 1000 | 10 | 55 SH. |
| 10-FS-200x100-55 | 200 | 100 | 1500 | 10 | 55 SH. |
| 10-FS-200x200-55 | 200 | 200 | 1200 | 18 | 55 SH. |

